

D.

DEFINITIVE TECHNOLOGY®



DEMAND SERIES | D15

High-Performance Tower Speakers

www.definitivetechology.com



SPECIFICATIONS

Dimensions (H x W x D)	1036 x 230 x 327mm
Cabinet only (H x W x D)	990 x 165 x 304mm
Product Weight	23.6kg
Tweeter	1 in / 25mm
Midrange	5.25 in / 133mm
Carbonfiber Woofer	5.25 in / 133mm
Bass Radiator	8 in / 200mm
Frequency Response (3dB limit)	48-22,000Hz
Sensitivity (2.83V/1m)	85 dB
Nominal Impedance	4 ohm
Crossover	450 / 2,500Hz
Recommended Amplifier Power	40 - 300 watts

EAN	Black	DEMANDD15LBK	0747192131968
	Black	DEMANDD15RBK	0747192131975
	White	DEMANDD15LWT	0747192132002
	White	DEMANDD15RWT	0747192132019

Definitive Technology Demand D15 high-performance tower speakers deliver full-range, room-filling sound and precise imaging from a modern, minimalistic design featuring an extruded Aluminium front baffle. Fill larger rooms with detailed Hi-Fi or home theatre sound with extended, controlled bass. The Demand Series outperforms the competition its price-class with more performance in a smaller form factor.

EXTENDED, CONTROLLED BASS WITH NO DISTORTION

Newly Designed Carbon Fiber Woofers

Carbon fiber offers greater rigidity to the cone for deeper and cleaner bass notes, while preventing cone distortion that can occur with other less rigid materials.

Dual Passive Radiators in Bipolar Configuration

Our engineers have 30 years of accumulated knowledge in bipolar speaker configurations, now applied to the Demand Tower speakers. Dual integrated side-firing passive radiators produce extended low-frequency reproduction free of port noise, from a smaller enclosure design.

Strong cabinet built, flexible placement to walls

Sophisticated cabinet bracing dramatically reduces vibration. Thanks to passive radiators instead of bass ports, speakers can be placed as close as you want to a wall, for maximum flexibility.

LARGE DYNAMICS

BDSS™ (Balanced Double Surround System) Midrange

The patented mid-range drivers provides greater linear excursion and output that results in superior mid-range detail and punchier bass compared to drivers of similar size. A 5.25" driver equals a 6.5" driver of other speakers in the price range.

WIDE, PRECISE SOUNDSTAGE

1" Aluminium Dome Tweeter with 20/20 Wave Alignment Lens™

Delivering a clear, precise high frequency response. The 20/20 Wave Alignment Lens smooths high frequencies off the tweeter for improved dispersion and a rich and balanced listening experience anywhere in your room.

Laterally Offset Tweeter Assembly

A unique sonic signature feature of the Demand Series, the tweeter is offset to deliver a more precise center stereo image and eliminate undesirable symmetric diffraction off the corners of the front baffle.

Linear Response Waveguide™

Patented Linear Response Waveguide extends both on and off axis frequency response, while improving dispersion for more natural midrange timbre and more precise imaging.